1

4. (Amended) A device according to claim 3, characterized in that the spring brake actuator [(6)] comprises

the clock spring [(14)], attached at its outer end to a spring brake actuator housing [(10)] and mechanically charged at a rotation of the actuator shaft [(11)] in a brake release direction,

an electric coil [(15)] for keeping - when electrically energized - the clock spring in its charged condition, and

transfer means [(12, 24, 18-22)] for transferring the rotative energy of the clock spring to the actuator shaft in a brake applying direction, when the coil is deenergized, but allowing free rotation of the shaft in either direction, when the coil is energized.

## Clean Version of Replacement Claims

- 1. A method for service braking a vehicle by means of a service brake actuator having a rotative motor, preferably an electric motor, as its service brake applying means, characterized in that energy from a loaded spring in a spring brake actuator connected to the service brake actuator is released at will for supplying supplementary service brake energy to the service brake actuator.
- 2. A device for carrying out the method of claim 1 for service braking a vehicle by means of a service brake actuator having a rotative motor, preferably an electric motor, as its service brake applying means, characterized by
- a spring brake actuator connected to the service brake actuator and containing a powerful spring and

control means for controlled release of energy from the spring when loaded, supplementary to the service brake energy supply from the service brake actuator.

- 3. A device according to claim 2, characterized in that the spring in the spring brake actuator is a clock spring or spiral spring.
- 4. A device according to claim 3, characterized in that the spring brake actuator comprises

## Page 3 Preliminary Amendment

the clock spring, attached at its outer end to a spring brake actuator housing and mechanically charged at a rotation of the actuator shaft in a brake release direction,

an electric coil for keeping - when electrically energized - the clock spring in its charged condition, and

transfer means for transferring the rotative energy of the clock spring to the actuator shaft in a brake applying direction, when the coil is deenergized, but allowing free rotation of the shaft in either direction, when the coil is energized.

Respectfully submitted,

Wesley W. Whitmyer, Jr., Reg. No. 33,558

Attorney for Applicant

ST.ONGE STEWARD JOHNSTON & REENS LLC

986 Bedford Street

Stamford, CT 06905-5619

203 324-6155